

Outdoor OptionsFor the HandReader Series

Schlage provides a full line of enclosures to protect your HandReader from the elements. Three different, proven solutions are available to ensure your Hand Reader performs and keeps performing regardless of your environment.

Hurricane

Constructed from high-impact linear low-density polyethylene. With a generous lid, the Hurricane enclosure offers protection from rain, and the contoured design facilitates water run-off. This enclosure has been designed so it can be added to an existing installation. When used with an integrated heater option (INT-HTR), it provides the ultimate solution for cold weather and exposure to the elements.

Tsunami

For the harshest environments, the Tsunami enclosure is water sealed and built to NEMA type 4 standards. The HandReader is protected from both splashing rain and hose-directed water, making it an ideal solution for industrial and food processing areas where hose-directed water is used for cleaning. In addition, when used with a heater-equipped HandReader (INT-HTR option), the Tsunami enclosure can withstand the bleakest of environments.



Hurricane



SPECIFICATIONS		
	Hurricane*	Tsunami*
Temperature Range	-20F to 120F -29C to 49C	-45F to 120F -43C to 49C
Environment	Provides significant protection from rain, sleet, snow, splashing water, falling dirt and windblown dust	Provides complete protection against rain, sleet, snow, splashing water, hose directed water, falling dirt and windblown dust when the door is closed
Dimensions H x W X D	14.0 in. x 12.0 in. x 10.5 in. 35.6 cm x 30.5 cm x 26.7 cm	23.0 in. x 14.0 in. x 11.5 in. 58.5 cm x 35.6 cm x 29.3 cm
Cross Weight (including reader)	11.5 lbs 5.3 kg	45.0 lbs 20.5 kg
HandReader	HandPunch 1000, 2000, 3000, 4000 HandKey II, and CR	HandPunch 1000, 2000, 3000, 4000 HandKey II and CR
Price	\$489	\$1,980

*with INT-NTR option

The Integrated Heater (INT-HTR Option)

The INT-HTR option includes an integrated heating element, a 24V power supply and an extended range LCD. The temperature-regulated heater element is built into the platen, where users place their hand, providing comfortable and trouble-free use even in the coldest environments. The heater is built directly into the HandReader. Therefore, it must be ordered at the same time the HandReader is ordered and is not field retrofittable. Although intended primarily for use with an enclosure, the INT-HTR option may be used in cooler environments where an enclosure is not required, such as an unheated warehouse.

Price: \$649

